

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : G06F 19/00	A1	(11) International Publication Number: WO 00/16230 (43) International Publication Date: 23 March 2000 (23.03.00)
(21) International Application Number: PCT/US99/21150 (22) International Filing Date: 15 September 1999 (15.09.99) (30) Priority Data: 60/100,777 17 September 1998 (17.09.98) US 09/282,047 29 March 1999 (29.03.99) US (71)(72) Applicants and Inventors: ARATOW, Michael [US/US]; 344 Bush Street, Mountain View, CA 94041 (US). SIMON, Robert, S. [US/US]; 45-21st Avenue, San Francisco, CA 94212 (US). (74) Agents: ASHBY, David, C. et al.; Flehr Hohbach Test Albritton & Herbert LLP, Suite 3400, 4 Embarcadero Center, San Francisco, CA 94111-4187 (US).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: AVIATION, TERRAIN AND WEATHER DISPLAY SYSTEM



(57) Abstract

A computer system (10) for displaying on a display device (30) terrain, weather and aviation information and including memory devices (16, 18, 20) which contain a terrain database, aviation map database, weather database, air traffic database, airplane specific database and route database. A processor (12) is coupled to the memory devices (16, 18, 20) and configured to determine a position and heading of an airplane over the terrain based on the route database, to compute terrain information, aviation map information, air traffic information and weather information relative to the airplane and to compute and display on the display device (30) flight parameters associated with the airplane using the airplane specific database. Advantages of the invention include the ability to supply a pilot with information that he can use to visualize his flight and approach to the destination airport.

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

AVIATION, TERRAIN AND WEATHER DISPLAY SYSTEM

REFERENCE TO RELATED APPLICATIONS

This application claims priority to Prov. Appl. No. 60/100,777 filed September 17, 1998.

5

FIELD

The present invention relates to an aviation, terrain, air traffic and weather display system that provides information for preflight and inflight use by pilots. In particular, the invention uses a terrain database, an aviation map database, a weather database, an airplane specific database, an air traffic control database and a route database to display a flight path over a given terrain while combining weather data (e.g. wind and clouds), aviation map data (e.g. control zones and required minimum visibilities and ceilings), air traffic data (e.g. position and movement vectors) and real time and/or predicted performance data (e.g. climb rate, endurance) to allow increased situational awareness of the pilot and enhance display of possible dangerous conditions and prohibited procedures.

15

BACKGROUND

Pilots have long needed assistance in making decisions whether to fly given ambient weather conditions (the "go/no go decision"). If that decision is positive, they must then determine the safety of flying to a given destination airport or along a preplanned route. Presently, the National Weather Service (NWS), Federal Aviation Administration (FAA) and other government agencies assist pilots by providing sky data including wind direction and speed, weather conditions such as rain and other

20

relevant data. Often this information is in cryptic form and is difficult for beginning pilots to understand. This information must then be applied in the context of a multitude of regulations and aircraft performance parameters, making this a formidable task. Moreover, experienced pilots still often find the information cryptic and find it difficult to retrieve and assimilate specific data relevant to their flight from the large amount available. Confounding the situation further, commercial flight operators have their own unique regulations and restrictions supplementing federal aviation regulations which must be recognized and adhered to by their pilots.

Some systems were developed to automate the delivery of weather information to pilots. For example, U.S. Pat. No. 5,265,024 describes a pilot's automated weather support system. The system receives weather information from a plurality of weather reporting organizations including the NWS, FAA and others. The system then converts the weather information into cross sections for preflight and inflight use. U.S. Pat. No. 5,432,895 describes a virtual reality imaging system. The system provides pilots with a representation of all the multidimensional space around an airport. This includes weather, air traffic and spatial relationships of the aircraft with respect to the airport and the ground level.

While these patents and other conventional products can provide some level of automation to the weather reporting, these systems do not take into account the special flight rules that are dictated for airports and airspace and specific flight parameters that are unique from one aircraft and one trip to the next.

What is needed is a system that combines information including weather, terrain, map, air traffic and airplane specific parameters to supply a pilot with information that he can use to visualize his departure, enroute segment and approach to the destination airport.

SUMMARY

The invention solves the identified problems by providing a computer system that displays terrain, weather, air traffic and aviation information. The invention provides pilots with information derived from a terrain database, an aviation map database, a weather database, an airplane specific database, an air traffic database and a route database. The system can display a flight path over a given terrain while combining aviation map data (e.g. approach paths and control zones), air traffic data

(position, direction, speed and predicted path) and weather data (e.g. wind and clouds). Further, the system can employ the airplane specific information along with the terrain, map, weather, air traffic and route information to display whether the airplane parameters will allow departure (e.g. minimum visibility/ceilings violated), flight
5 along the route or landing at a specific airport (e.g. crosswind component too large). If the pilot desires, the system can suggest alternate routes and alternate airports. Of course, the pilot makes the decision whether to accept the system's suggestions (many of whose parameters are controlled by the pilot) and whether to query the system to provide additional options.

10 Three important features of the system are the aviation map database, the airplane specific database and the air traffic database. The aviation map database provides flight information such as restricted airspace, location of airports, location of VORs, instrument approach/departure paths and other information. The aviation map database also provides information on airports such as runway lengths, runway
15 elevations, runway orientation, alternate airports and other information. This information is very important for preflight and inflight planning.

The airplane specific database provides information on a specific aircraft such as runway length requirements, maximum crosswind component, fuel consumption, maximum climb speed and rate, object clearance, current speed and direction, outside
20 air temperature and other information. This information is combined with information from the other databases to be used for preflight and inflight planning.

The air traffic database provides information on aircraft type, position, speed, direction and predicted position that are in the area of the designated flight. Combined with information from the other databases, this can be used for inflight planning and
25 collision avoidance.

An exemplary embodiment of the system includes a terrain database, an aviation map database, a weather database, an airplane specific database, an air traffic database and a route database. A processor is coupled to the terrain database, the aviation map database, the weather database, the airplane specific database, an air
30 traffic database and the route database and configured to determine a position and heading of an airplane over the terrain based on the route database, to compute and display terrain information, aviation map information, air traffic information and weather information relative to the airplane and to compute and display flight

parameters associated with the airplane using the airplane specific database and the route database.

Advantages of the invention include the ability to supply a pilot with information that he can use to visualize his flight and approach to the destination airport. The pilot can also visualize which flying variables (e.g. required climb rate, wind speed/direction) are beyond the aircraft's capabilities or are prohibited by federal regulations (e.g. visibilities below minimums). This provides improved information to the pilot so that he can make his decision whether to make to flight or whether to choose his intended route or destination. With this improved information, the pilot will make safe and informed decisions about flying.

BRIEF DESCRIPTION OF THE FIGURES

Additional advantages of the invention will become apparent upon reading the following detailed description and upon reference to the drawings, in which:

Figure 1 depicts a computer system 10 according to an embodiment of the invention;

Figure 2 depicts a memory structure for storing program and data in the computer system of Figure 1;

Figures 3A-F depict the database system of Figure 2 in greater detail;

Figure 4 is a functional block diagram according to an embodiment of the invention;

Figures 5A-I depict a user display interface according to an embodiment of the invention.

Figure 6 depicts an aspect of the invention for retrieving and updating the database system;

Figure 7 depicts an aspect of the invention for retrieving and updating the weather database;

Figure 8 depicts an aspect of the invention for retrieving and updating the map database with NOTAM data; and

Figure 9 depicts an aspect of the invention for retrieving and updating the air traffic database.

DETAILED DESCRIPTION

Exemplary embodiments are described with reference to specific configurations. Those skilled in the art will appreciate that various changes and modifications can be made while remaining within the scope of the claims.

5 Figure 1 depicts a computer system 10 according to an embodiment of the invention. The computer system includes a processor (CPU) 12 coupled to a bus 14. A memory including a RAM 16, a hard disk 18 and CD-ROM 20 is also coupled to the bus 14 and accessible by the processor. The memory is configured to store programs and data necessary for the invention, as described below. A number of interfaces 22,
10 24, 25, 26 are provided for coupling to a user interface. The user interface includes a display 30 a keyboard 32 and an input device 34. The input device 34 can be a mouse, touchscreen, joystick, flight pedals and yoke, or other conventional input device. A communications interface 28 is configured to communicate with other computer systems 36 such as those of the National Weather Service (NWS), Federal Aviation
15 Administration (FAA), Internet, commercial vendors or other computers. The communications interface is designed to retrieve and translate information from these sources. Of course, additional or alternative computer elements can be employed, as known in the art.

 In an in-flight system, an interface 27 is provided for a global positioning
20 receiver (GPS) 29 in order to provide aircraft position information to the computer system 10. An interface 25 is created for any onboard aircraft sensors such as wind direction and speed, outside air temperature, aircraft attitude and air speed in order to further supplement navigation and weather information to the computer system 10. This type of real time position, aircraft and weather information can assist pilots and
25 navigators in developing flight plans and deciding on alternate airports, if necessary. Weather and air traffic data reside on a server and the information is sent to transmission stations for dissemination either via the Internet or another communications medium such as microwave or radio. In the in-flight system, the communication interface 28 may be a wireless interface that receives weather and air
30 traffic updates from ground stations. As the aircraft moves through space, the computer uses GPS position updates to display the new x, y, z position of the aircraft in relation to the terrain, other air traffic, associated weather, and aviation data. As new weather and air traffic data are received, the computer system displays the aircraft

and local traffic at the appropriate positions with the appropriate new surrounding weather conditions. The pilot can look ahead and behind as necessary to make flight decisions.

Figure 2 depicts a memory 40 structure for storing program and data in the computer system 10 of Figure 1. The memory 40 is divided into three primary components: a user interface system 42, database system 44 and communication system 46.

The user interface system 42 includes routines 48-52 for receiving information from the user and for providing information to the user. Initialization routine 48 provides a function that initializes the computer system 10 on power up and presents the user with a start-up display. A user input routine 50 is configured to receive commands from the user via the user interface and to conform the commands to applicable computer instructions. For example, if the user instructs the computer system 10 to display an alternate image, the user input element instructs the processor 12 to execute such a command. A user output routine 52 is configured to provide the user with an output from the computer system 10. For example, a display will provide the user with a selected alternate image. Moreover, the output routine can provide additional user stimulus such as force feedback or spatialized or nonspatialized auditory alarms to alert the pilot to certain conditions such as turbulence, icing, high velocity winds or an impending collision with terrain or another aircraft.

The database system 44 includes databases for storing the information related to the invention. Figures 3A-F depicts the database system in greater detail.

Figure 3A depicts the terrain database 54 that stores data relating to the ground terrain. The database stores latitude, longitude and elevation for a predefined area. The area is broken into cells that represent the terrain. A number of cells are stored in the memory 16, 18 and 20 and additional cells can be added and updated via the CDROM 20 or communication interface 28.

Figure 3B depicts the map database 56 that stores aviation map features. Airspace information is provided including: class A, B, C, D, E, G airspace locations and altitudes; prohibited airspace, restricted airspace, warning areas, military operation areas and alert areas locations, altitudes and times of active status; parachute jumping, ultralight, and glider area locations; and military training routes locations, altitudes and times of operation. Regarding obstacles, location and height information is important.

Information about navigational aids' locations, frequencies and types is provided. Other aviation map features include airport location, hours of operation, runways with orientation length and type (e.g. asphalt, grass or other material), and traffic pattern information. NOTAM types L, D, and FDC are stored in the database depending on
5 date/time in which they are in effect, location(s)/object(s) affected, and action upon the object(s) or amendment made. For instrument flight, specific information is important such as standard departures, standard terminal arrivals and instrument approaches including: landing patterns, published headings, altitudes, and fixes (and their locations), approach type, decision height (DH) or minimum decent altitude (MDA),
10 aircraft category specific data (DHs, MDAs, minimum visibility and ceiling), required climb rates and decent profiles and times to final approach fix. These data may also be customized to reflect commercial operator specific minimums and requirements for landing, takeoff or alternate destinations. For pre-flight and in-flight planning, airway location is provided including names and intersections as well as landmark types,
15 names, locations and elevations. This map database provides the pilot with information to make pre-flight and in-flight planning.

Figure 3C depicts the weather database 58 that stores weather information based on latitude, longitude and altitude. Some of the weather characteristics are: surface observations; composite moisture stability data; wind shear reports and
20 forecasts; icing forecasts; turbulence reports; pilot reports; constant pressure chart data; volcanic ash forecast and dispersion data; surface analysis data; radar summary data; significant weather prognostic data; and satellite imagery (e.g. GOES, NEXRAD). This database can be populated by any future reporting or forecasting data products and translated into designated shapes or icons and placed by geospecific
25 coordinates in the 3D world display.

Figure 3D depicts the aircraft database 60 that stores aircraft specific parameters for various aircraft. For each type of aircraft, various parameters are stored including: takeoff performance and distance for different configurations and
departures; landing performance and ground roll for different configurations and
30 arrival profiles; cross-wind limits; weight and balance; cruise speed; service ceiling; rate of climb; angle of climb; stall speed; engine out glide path, speed and distance; fuel capacity; gas consumption; and other parameters. This information assists the computer system 10 and the pilot in making pre-flight and in-flight planning. For

example, by using the ground wind information from the weather database and the runway orientation from the map database, the computer can calculate the cross-wind component of the current wind for a particular runway and inform the pilot whether it is within the allowed parameters for the aircraft.

5 Figure 3E depicts the route database 62 that stores information specified by the user including flight path information. This database is slightly different than the others because it is intended to be modified extensively by the user. For example, the user can input, retrieve and modify flight path parameters. Additionally, for in-flight use, the route and weather is modified by the GPS position information and aircraft
10 sensors via interfaces 27 and 25.

 Figure 3F depicts the traffic database that stores specific parameters associated with other aircraft flying in the area of the pilot. For each aircraft, various parameters such as position (x, y, z), speed, reported flight route and type of aircraft are stored. The information assists the computer system 10 and the pilot in displaying local air
15 traffic conditions and allows prediction of flight paths from current position and speed parameters of other aircraft in the air traffic database and of the pilot's aircraft from the route database (GPS and planned route) to identify potential collisions.

 Figure 4 is a functional block diagram according to an embodiment of the invention. A fusion module is employed to identify and retrieve information from the
20 database system. In particular, the fusion module is coupled to the weather database, terrain database, the air traffic database, the aviation map database, the airplane specific database and the route database and configured to determine a position and heading of an airplane over the terrain based on the route database, to compute terrain information, weather information, air traffic information and aviation map information
25 relative to the airplane and to compute and display flight parameters associated with the airplane using the airplane specific database.

 Figures 5A-H depict a user display interface according to an embodiment of the invention. Figure 5A depicts a cockpit view while flying in the San Francisco bay area. San Francisco airport (SFO) is identified along with its runways and the
30 barometric pressure 30.02. To the left of the display window 5A-1 is an information group 5A-2 providing information on the chosen airport (SFO) such as runway length and heading as well as airport latitude and longitude. Other airports such as Palo Alto (PAO) are identified along with their runway and barometric pressure information. An

altitude indicator is provided along the left side of the display window 5A-1 and a heading indicator along the top side of the display window 5A-1. The airports can be identified with attributes to indicate whether they are acceptable takeoff or landing sites for the aircraft (e.g. crosswind parameters within limits and runway length withing limits, etc). For example, runways are shaded with green overlay for distances calculated to be less than or equal to runway length minus 50 feet, shaded with yellow overlay for distances calculated to be greater than runway length minus 50 feet and less than or equal to runway length, and shaded with red for distances calculated to be greater than the runway length. Additionally, the length of the overlays correspond to the calculated takeoff/landing distances.

The display window 5A-1 is the 3D portion of a general user display containing data presented as a combination of 2D and 3D display techniques. The display is provided on the user's display 30, but can also be implemented through software running on a dedicated hardware device such as a personal computer (PC), or on a web page running on a PC. The user has control of all the display elements so any combination of parameters may be turned on or off. Three display profiles are created covering the takeoff, en route and landing or approach sequences of a flight for usability. Additionally, extensive use of an event trigger function, which allows an event to be triggered when the cursor is over an object, allows the user to selectively drill down on information on the 2D or 3D display by providing supplemental textual information right at the cursor or in a text box in the display window 5A-1.

Within the display window 5A-1 is the terrain information such as mountains and water. Adjacent to the display window is weather information 5A-3 such as visibility, dewpoint spread, a ball bearing-like representation of temperature and wind, and other information. This weather information can also be overlaid on the display window 5A-1 or an icon can be provided to open and close the weather information.

Figure 5B depicts a satellite view of the aircraft, terrain and weather conditions. As shown, the aircraft is heading toward a group of clouds that are identified as gray areas. These clouds can be displayed by altitude, water density, etc. by methods inherent to the imaging system used (e.g. NEXRAD, GOES-9) such as color-coding the cloud in proportion to water content (e.g. NEXRAD) or other similar technique (see Figure 5E for a specific example of a NEXRAD image).

Figure 5C depicts the ball bearing-like representation of temperature, wind and pressure. Each small circle presented around the circumference represents temperature or pressure at the designated altitude. The center ball is the closest reported temperature to the user's position in the 3D environment and can be interpolated
5 between the two closest values. The line from the center of the circle pointing outward (like the hand of a clock) shows the aircraft altitude in the 3D environment (also represented on left border of the window 5A-1). The balls are filled with color in proportion to the magnitude of the temperature or pressure (a red ball representing a temperature such as 80 degrees Celsius) and the color will travel through a gradation
10 of blue, green, yellow, and red (red being the hottest). Also in the center or on the periphery will be the time that the readings are valid expressed in the units of fractional hours from present time.

The format for wind is similar, except the balls are replaced with the 3D arrows. This graphic is displayed within the 3D environment (and its position
15 adjustable) because the face is preferably presented to the user while the arrows remained fixed in orientation to show the wind's direction relative to the user's position in 3D space. As above, a space near the center arrow also has the time that the readings are valid expressed in the units of fractional hours from present time. This wind designator alternatively may be positioned in the 2D portion of the display
20 and the arrows positioned such that they display wind relative to the pilot's aircraft as if one was looking down from above the aircraft (i.e. bird's eye view).

Figure 5D depicts a cloud coverage legend that describes the degree of cloud coverage to the user. These symbols appear in the 3D world at their reported site adjacent to altitude values specifying ceiling elevations. Figure 5E is an enlargement
25 of one of the types of displays shown in Figure 5B which depicts a NEXRAD weather image to assist the user in identifying local weather conditions. Figure 5F depicts an icon used to express wind conditions at the surface and can be used in the ball bearing representation. Figure 5G depicts a representation of clouds near a reporting station. For each of the designated altitudes, the cloud bases are represented by a
30 semitransparent disk at the reported altitude and accompanied by a cloud coverage symbol for each layer. Figure 5H is a legend that provides information about the radio aids to navigation. These are represented as 3D shapes in the 3D environment with cross sections which are similar in appearance to the symbols in the legend. Since the

radio aids are displayed in the display window 5A-1, the user can pop-up legends such as that of Figure 5H to ascertain the meaning of various map indicia.

Figure 6 depicts an aspect of the invention for retrieving and updating the database system. The communication system is important since much of the
5 information used in the database is periodically updated. For example, terrain data is updated when a new building is raised, map data is updated when a new airspace type is added or modified and airplane specific data is updated when new airplanes are specified. This type of information can be updated weekly or daily. However, some
10 of the information is much more time-critical, such as weather data, certain types of notice data (e.g. NOTAMs) and air traffic data. For example, weather data is updated when fog builds on the coast or a weather front passes through an area, NOTAMs are updated whenever an important notice is posted by the FAA and air traffic data is updated continuously.

The terrain data, map data and airplane specific data updates can be performed
15 periodically (e.g. weekly or daily), however, weather data is critical and must be updated very often, such as hourly or less, NOTAM data must be updated whenever an important notice is posted and air traffic data must be updated continuously. While most of the updates can be translated into the specific database format as needed and the data formats can be re-engineered periodically, weather data, NOTAM data and air
20 traffic data must be accepted in data formats that are available and that become available. For these reasons, weather data receipt and conversion, NOTAM data receipt and conversion and air traffic receipt and conversion are described here in detail.

Figure 7 depicts the weather data receipt and conversion module. The National
25 Weather Service (NWS), National Oceanic and Atmospheric Administration (NOAA) and Federal Aviation Administration (FAA) issue weather related reports and these reports are available by connecting to a computer network. There are several types of reports available including hourly and special weather observation reports, terminal aerodrome forecasts, automated or manual surface observations (METARs), aviation
30 area forecasts, winds aloft reports, radar reports, pilot reports, severe weather forecasts, AIRMETS, SIGMETS, and others. These reports identify the type of report, the report location, the time of the report and the weather. Often the weather is a weather string that includes a large amount of cryptic information such as BKN for broken clouds and

OVC for overcast clouds. A translation module takes the reports and converts them to data that can be stored in the database. The translation module includes a list of all the cryptic information and a conversion routine that performs the translation.

Figure 8 depicts the notice data receipt and conversion module. Notice data is also updated, although not as often, but this information is important to navigation and safe flying procedures. This data must also be accepted in data formats that are available and that become available. For these reasons, NOTAM data receipt and conversion is described here in detail. NOTAM types L, D, and FDC are handled using a different translation module. Many of these reports are associated with airports, nav aids, airspace etc. and can be identified in the 3D environment by a tag such as the letters "NOTAM" or the letter "N" floating near such objects. A mouse-over action on any of these tagged objects or the tag will produce a textual display of the NOTAM in a 2D window. Information which can readily be displayed in the 3D environment ("passed through") will be implemented at the valid date and time of the NOTAM. There is no action necessary to display this type of NOTAM as it is part of the display. An example of this would be a runway closure. As runways are already modeled in the 3D world, a red "X" over the runway would indicate closure, and no additional notation or mouse actions need be performed. Because NOTAMs must be accepted in data formats which are available and become available, the following is a more detailed account of the translation module implementation. Valid dates, times and locations of the NOTAMS will be parsed initially. If these occur in the area and during the time of the proposed or actual flight, they are labeled as active, otherwise they are stored in the database with a flag to become active at the valid time and date. Nav aids, airports, runways, taxiways, lighting aids and obstructions in the 3D world will be tagged with an icon denoting a NOTAM is in effect for that object. Clicking on the object would show the NOTAM effects (if not already implemented in the 3D world) and give a textual display simultaneously in a 2D text box. For example, if a nav aid had an unusable section of its service area from one altitude to another, this would be displayed as a red floating wedge in the area affected after clicking on the tagged object. If a runway lighting system is out of service, clicking on the NOTAM tag or the runway associated with the tag would trigger a pop up window displaying a 2D graphic of the lighting system with red Xs on it. If parachuting or demonstration aircraft are to be in a specific vicinity as reported by a NOTAM, clicking on the

NOTAM tag or associated airport will display a semitransparent cylinder with an associated parachute or aircraft icon marking the area of involvement. Certain NOTAMs are passed through to the 3D world for direct implementation without the user having to prompt the display. These include NOTAMs for nav aids out of service
5 (a red "X" on the 3D object representing the nav aid), obstructions in or around the airport vicinity (an obstruction icon would be drawn directly into the 3D environment at its location) or changes in approach/departure or alternate minimums (shown directly when the pilot calls for approach/departure paths to be displayed).

Once the information has been stored in the weather database (for weather
10 data) or map database (for NOTAM data), the invention can display the weather or NOTAM changes on the display in the user interface. In this manner, the user can visually see the weather conditions or NOTAM changes along a predetermined route or any route of their choosing and at one or more destination airports.

*Figure 9 depicts the air traffic data receipt and conversion module. The
15 communication system is important because most of the information used in the database is updated regularly at short intervals. For these reasons, air traffic data receipt and conversion is described here in detail. Information available from the FAA Radar, Air Route Traffic Control Center (ARTCC), and the Air Route Traffic Control Command Center (ARTCCC) databases of current IFR or other monitored aircraft
20 include the aircraft type, aircraft N number, date and time of data capture, aircraft global position, aircraft speed, aircraft heading, aircraft flight plan and flight plan modifications or transient deviations for events such as weather. These data are captured, parsed and translated into a format enabling population of the air traffic database as, shown in Figure 9. A calculation module determines the current and
25 future paths of each aircraft using position, heading and flight plan information, and the database will be updated accordingly. As each aircraft is tracked, a user toggled feature will allow tracing of other aircrafts' path through 3D space in the virtual world display. An arrow emanating from each aircraft depicts the immediate direction and position in the next several seconds, as shown by Figure 5I arrow 82. Heading and
30 speed information can be displayed either through a toggle feature or a mouse-over gesture. Using both this information and flight plan and speed data, predicted paths can be drawn from any aircraft and a collision algorithm can determine any path intersections to occur, as shown by Figure 5I arrow 84. Users may toggle on an

immediate predicted path function represented by a different colored arrow or different color and/or thickness pathway line drawn up to a minute in the future, or they may select collision detection of pathways extrapolated up to 30 minutes into the future. By accounting for speed, position, heading and flight plan, potential path collisions
5 can be identified and affected pathways can be highlighted or displayed by a flashing pattern, as shown by Figure 5I path 86. A prominent icon 88 at the anticipated collision point can also be displayed. In this manner, the system provides important information to insure that the pilot has enhanced situational awareness of the immediate and potential air traffic conflicts within the route of flight.

10 Advantages of the invention include the ability to supply a pilot with an enhanced situational awareness through data display in visual or other formats so that he can visualize and analyze his flight and approach to the destination airport. This provides improved information to the pilot so that he can quickly and more easily make his decision whether to make to flight or to make an approach or takeoff. With
15 this improved information, the pilot will make safe and informed decisions about flying.

Having disclosed exemplary embodiments and the best mode, modifications and variations may be made to the disclosed embodiments while remaining within the scope of the invention as defined by the following claims.


CLAIMS

What is claimed is:

1. A computer system for displaying terrain, weather and aviation information, comprising:
 - 5 a terrain database;
 - an aviation map database;
 - a weather database;
 - an air traffic database;
 - an airplane specific database;
 - 10 a route database; and
 - a processor coupled to said terrain database, said aviation map database, said weather database, said air traffic database, said airplane specific database and said route database and configured to determine a position and heading of an airplane over said terrain based on said route database, to compute terrain information, weather
 - 15 information and aviation map information relative to said airplane and to compute and display flight parameters associated with said airplane using said airplane specific database.
2. The computer system of claim 1, for further displaying for displaying air traffic information, further comprising:
 - 20 an air traffic database; and
 - wherein said processor is coupled to said air traffic database and configured to compute air traffic information relative to said airplane and to compute and display flight parameters associated with said airplane using said airplane specific database.
3. The computer system of claim 1, wherein:
 - 25 said aviation map database includes control zones, restricted airspace, location of airports and location of VORs, instrument arrival/departure procedures and airway routes.
4. The computer system of claim 3, wherein:
 - 30 said aviation map database includes airport information including runway lengths, runway altitudes, runway orientation and alternate airports.

5. The computer system of claim 1, wherein:
said airplane specific database includes runway length requirements, maximum crosswind component, fuel consumption, maximum climb speed, service ceiling, weight and balance parameters and object clearance.
- 5 6. The computer system of claim 3, wherein said air traffic database includes aircraft type, speed, direction, altitude, reported flight plan and predicted position and speed.
7. A method of displaying terrain, weather and aviation information related to an aircraft in response to a user's input, comprising the steps of:
- 10 receiving the user's input including location information;
identifying a location of the aircraft;
retrieving terrain data from a terrain database;
retrieving map data from an aviation map database;
retrieving weather data from a weather database;
- 15 retrieving airplane specific data from an airplane specific database;
retrieving route data from a route database; and
based on the user's input, determining a position and heading of an airplane over the terrain based on the route database;
computing terrain information, weather information and aviation map
- 20 information relative to the airplane and computing and displaying flight parameters associated with the airplane using the airplane specific database.
8. The method of claim 7 for further displaying air traffic information, further comprising the steps of:
- retrieving air traffic data from an air traffic database; and
- 25 computing air traffic information relative to the airplane and computing and displaying flight parameters associated with the airplane using the airplane specific database.

9. A method of translating weather information from a database having a first format and converting the weather information to a database having a second format, said method comprising the steps of:
- receiving weather information from the first database in the first format;
 - 5 associating keywords in the first format with keywords in the second format;
 - identifying locations in the first format and converting the locations to latitude and longitude; and
 - storing the keywords in the second format and locations in the second database in the second format.
- 10 10. A method of translating air traffic information from a first database having a first format and converting the air traffic information to a second database having a second format, said method comprising the steps of:
- receiving air traffic information from the first database in the first format;
 - associating keywords in the first format with keywords in the second format;
 - 15 identifying locations, speeds, and directions in the first format and converting the locations to latitude and longitude, speeds to knots, directions into degrees of azimuth, planned routes into vectors; and
 - storing the keywords in the second format and locations, speeds, directions and planned routes in the second database in the second format.



40		
	USER INTERFACE SYSTEM	42
	Initialization	48
	User Input	50
	User Output	52
	DATABASE SYSTEM	44
	Terrain	54
	Map	56
	Weather	58
	Aircraft	60
	Route	62
	Air Traffic	64
	User Specified	66
	COMMUNICATION SYSTEM	46
	NWS	68
	FAA	70
	NOAA	72
	Commercial Vendor	74
	Internet	76
	Other	78

FIG. 2

Terrain Database	54
cell 1 lat, long, elevation	
cell 2 lat, long, elevation	
cell 3 lat, long, elevation	
cell 4 lat, long, elevation	
.....	

FIG. 3A

Map Database	56
uncontrolled airspace, location	
controlled, location	
airport, location	
runway	
orientation	
length	
pattern information	
obstacles	
hours of operation	
runway material	
navaid	
location	
type	
frequency	
NOTAMS	
effective date(s)	
effective time(s)	
location	
type	
object or location affected	
action on object or location	
regulation/procedure affected	
amendment to regulation/procedure	
Instrument Approaches/Departures	
initial approach fix(es) position (x,y,z)	
fix(es) position (x,y,z)	
path (x,y,z)	
decision height/missed approach point	
aircraft category A,B,C,D	
minimums	
aircraft category A,B,C,D	
visibility	
ceiling	
alternate airports	
missed approach procedure	
path (x,y,z)	
fixes (x,y,z)	
holding pattern (x,y,z)	

FIG. 3B

Weather Database	58
time	
sky condition, location	
visibility, location	
cloud base elevation, location	
wind speed and direction, location	
REPORT TYPES	
HOURLY/SPECIAL WEATHER OBSERVATIONS (METAR)	
TERMINAL AERODROME FORECASTS (TAF)	
AVIATION AREA FORECASTS	
WINDS ALOFT FORECASTS	
RADAR REPORTS	
PILOT REPORTS	
SEVERE WEATHER FORECASTS	
AIRMETS	
SIGMETS	

FIG. 3C

Aircraft Database	60
Aircraft type A	60a
takeoff performance	60a-1
distance	60a-2
speed	60a-3
landing performance	60a-4
ground roll	60a-5
max crosswind component	60a-6
cruise speed	60a-7
single engine	60a-8
multiengine	60a-9
service ceiling	60a-10
single engine	60a-11
multiengine	60a-12
rate of climb	60a-13
single engine	60a-14
multiengine	60a-15
angle of climb	60a-16
stall speed	60a-17
glide path	60a-18
speed	60a-19
distance	60a-20
fuel capacity	60a-21
current fuel amount	60a-22
fuel consumption	60a-23
current fuel consumption	60a-24
current weight	60a-25
maximum gross weight	60a-26
maximum takeoff weight	60a-27
maximum landing weight	60a-28
useful load	60a-29
moment	60a-30
position 1	60a-31
weight	60a-32
.....	
Aircraft type B	60b
.....	
Aircraft type C	60c
.....	

FIG. 3D

Route Database	62
start location and speed	62a
vector A, time A	62b
vector B, time B	62c
.....	62d
end location, time end	62e

FIG. 3E

Air Traffic Database	64
Aircraft A	64a
N number	64a-1
type	64a-1
position (x,y,z)	64a-2
speed	64a-3
reported flight path (flight plan)	64a-4
predicted flight path (calculated)	64a-5
Aircraft B	64b
.....	64b-...
Aircraft C	64c
.....	64c-...

FIG. 3F




FIG. 4




FIG 5A




Fig 5c



FIG 5 D






Fig 5E








Fig 5H




FIGURE 5I




FIG. 6

WEATHER DATA RECEIVING AND TRANSLATING MODULE




FIG. 7

NOTAM DATA RECEIVING AND TRANSLATING MODULE

Data From NATCOM, FAA


report
location
time

FIG. 8

AIR TRAFFIC DATA RECEIVING AND TRANSLATING MODULE




FIG. 9

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US99/21150

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :GO6F 19/00

US CL :701/14, 120

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 701/14, 120; 340/971, 973; 702/3; 707/101, 104

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

USPAT, EPABS, JPABS, WPI

search terms: aircraft, airplane, aviation, aerodyne, wealtier, database, keyword, format?, terrain, traffic, conver?, translat?

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	GEORGE, F., Introducing Primus Epic, Business & Commercial Aviation, November 1996, see pages 116-120	1-8
Y	HOLAHAN, J., LCDs, Mice on the Flight Deck!, Aviation International News, 01 November 1996, see pages 56-58	1-8
Y	SCOTT, W.B., Pentium Powers 'Epic' Integrated Avionics, Aviation Week & Space Technology, 18 November 1996, see pages 67-69	1-8
Y	DITTER, A., An Epic in the Making, Commuter World, December 1996-January 1997, see pages 16, 18-21	1-8



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
B earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*A* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

16 DECEMBER 1999

Date of mailing of the international search report

02 FEB 2000

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

MICHAEL J. ZANELLI

Telephone No. (703) 308-1113

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US99/21150

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4,827,419 A (SELBY, III) 02 May 1989, see col. 2, line 65 to col. 3, line 2; col. 7, line 20 to col. 8, line 66; col. 10, lines 62-65; col. 11, lines 19-26; col. 18, line 43 to col. 19, line 4; col. 19, 67 to col. 20, line 6	9
A	US 5,265,024 A (CRABILL et al.) 23 November 1993	9
A	US 5,111,400 A (YODER) 05 May 1992	9,10

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)